Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

Jameco Part Number 23966TI

- **Wide Range of Supply Voltages:**
  - **Single Supply . . . 3 V to 30 V (LM2904 and LM2904Q . . . 3 V to 26 V) or**
  - **Dual Supplies**
- **Low Supply-Current Drain Independent of Supply Voltage . . . 0.7 mA Typ**
- **Common-Mode Input Voltage Range Includes Ground, Allowing Direct Sensing Near Ground**
- **Low Input Bias and Offset Parameters:**
  - **Input Offset Voltage . . . 3 mV Typ**
    A Versions . . . 2 mV Typ
  - **Input Offset Current . . . 2 nA Typ**
  - **Input Bias Current . . . 20 nA Typ**
    A Versions . . . 15 nA Typ
- **Differential Input Voltage Range Equal to Maximum-Rated Supply Voltage . . . ±32 V (LM2904 and LM2904Q . . . ±26 V)**
- **Open-Loop Differential Voltage Amplification . . . 100 V/mV Typ**
- **Internal Frequency Compensation**

D, JG, P, OR PW PACKAGE
(TOP VIEW)



LM158, LM158A . . . FK PACKAGE
(TOP VIEW)



NC – No internal connection

description

These devices consist of two independent, high-gain, frequency-compensated operational amplifiers designed to operate from a single supply over a wide range of voltages. Operation from split supplies also is possible if the difference between the two supplies is 3 V to 30 V (3 V to 26 V for the LM2904 and LM2904Q), and V_{CC} is at least 1.5 V more positive than the input common-mode voltage. The low supply-current drain is independent of the magnitude of the supply voltage.

Applications include transducer amplifiers, dc amplification blocks, and all the conventional operational amplifier circuits that now can be more easily implemented in single-supply-voltage systems. For example, these devices can be operated directly from the standard 5-V supply used in digital systems and easily provides the required interface electronics without additional ±5-V supplies.

The LM2904Q is manufactured to demanding automotive requirements.

The LM158 and LM158A are characterized for operation over the full military temperature range of –55°C to 125°C. The LM258 and LM258A are characterized for operation from –25°C to 85°C, the LM358 and LM358A from 0°C to 70°C, and the LM2904 and LM2904Q from –40°C to 125°C.

logic diagram (each amplifier)



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

Copyright © 1998, Texas Instruments Incorporated
On products compliant to MIL-PRF-38535, all parameters are tested unless otherwise noted. On all other products, production processing does not necessarily include testing of all parameters.

AVAILABLE OPTIONS

T_A	$V_{IO(max)}$ AT 25°C	PACKAGED DEVICES					CHIP FORM (Y)
		SMALL OUTLINE (D)†	CHIP CARRIER (FK)	CERAMIC DIP (JG)	PLASTIC DIP (P)	TSSOP (PW)‡	
0°C to 70°C	7 mV	LM358D	—	—	LM358P	LM358PW	LM358Y
	3 mV	—	—	—	LM358AP	—	—
–25°C to 85°C	5 mV	LM258D	—	—	LM258P	—	—
	3 mV	—	—	—	LM258AP	—	—
–40°C to 125°C	7 mV	LM2904D	—	—	LM2904P	LM2904PW	—
		LM2904QD	—	—	LM2904QP	—	—
–55°C to 125°C	5 mV	LM158D	LM158FK	LM158JG	LM158P	—	—
	2 mV	—	LM158AFK	LM158AJG	—	—	—

† The D package is available taped and reeled. Add the suffix R to the device type (e.g., LM358DR).
‡ The PW package is only available left-end taped and reeled.

schematic (each amplifier)



COMPONENT COUNT	
Epi-FET	1
Diodes	2
Resistors	7
Transistors	51
Capacitors	2

LM358Y chip information

These chips, when properly assembled, display characteristics similar to the LM358. Thermal compression or ultrasonic bonding can be used on the doped-aluminum bonding pads. Chips can be mounted with conductive epoxy or a gold-silicon preform.

BONDING PAD ASSIGNMENTS





Chip Thickness: 15 Typical
Bonding Pads: 4 × 4 Minimum
$T_{J(max)}$ = 150°C
Tolerances Are ±10%.
All Dimensions Are in Mils.
No Backside Metallization
Pin (4) is Internally Connected to Backside of Chip.

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

		LM158, LM158A LM258, LM258A LM358, LM358A	LM2904 LM2904Q	UNIT
Supply voltage, V_{CC} (see Note 1)		32	26	V
Differential input voltage, V_{ID} (see Note 2)		±32	±26	V
Input voltage, V_I (either input)		–0.3 to 32	–0.3 to 26	V
Duration of output short circuit (one amplifier) to ground at (or below) 25°C free-air temperature ($V_{CC} \le 15$ V) (see Note 3)		Unlimited	Unlimited	
Continuous total power dissipation		See Dissipation Rating Table		
Operating free-air temperature range, T_A	LM158, LM158A	–55 to 125		°C
	LM258, LM258A	–25 to 85		
	LM358, LM358A	0 to 70		
	LM2904, LM2904Q		–40 to 125	
Storage temperature range, T_{stg}		–65 to 150	–65 to 150	°C
Case temperature for 60 seconds	FK package	260		°C
Lead temperature 1,6 mm (1/16 inch) from case for 60 seconds	JG package	300	300	°C
Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds	D, P, or PW package	260	260	°C

NOTES: 1. All voltage values, except differential voltages and V_{CC} specified for measurement of I_{OS}, are with respect to the network ground terminal.
2. Differential voltages are at IN+ with respect to IN–.
3. Short circuits from outputs to V_{CC} can cause excessive heating and eventual destruction.

DISSIPATION RATING TABLE

PACKAGE	$T_A \le 25°C$ POWER RATING	DERATING FACTOR ABOVE $T_A = 25°C$	$T_A = 70°C$ POWER RATING	$T_A = 85°C$ POWER RATING	$T_A = 125°C$ POWER RATING
D	725 mW	5.8 mW/°C	464 mW	377 mW	145 mW
FK	1375 mW	11.0 mW/°C	880 mW	715 mW	275 mW
JG	1050 mW	8.4 mW/°C	672 mW	546 mW	210 mW
P	1000 mW	8.0 mW/°C	640 mW	520 mW	200 mW
PW	525 mW	4.2 mW/°C	336 mW	273 mW	–

electrical characteristics at specified free-air temperature, V_{CC} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS†		T_A‡	LM158 LM258			LM358			UNIT
					MIN	TYP§	MAX	MIN	TYP§	MAX	
V_{IO}	Input offset voltage	V_{CC} = 5 V to MAX, $V_{IC} = V_{ICR(min)}$, V_O = 1.4 V		25°C		3	5		3	7	mV
				Full range			7			9	
α_{VIO}	Average temperature coefficient of input offset voltage			Full range		7			7		µV/°C
I_{IO}	Input offset current	V_O = 1.4 V		25°C		2	30		2	50	nA
				Full range			100			150	
α_{IIO}	Average temperature coefficient of input offset current			Full range		10			10		pA/°C
I_{IB}	Input bias current	V_O = 1.4 V		25°C		–20	–150		–20	–250	nA
				Full range			–300			–500	
V_{ICR}	Common-mode input voltage range	V_{CC} = 5 V to MAX		25°C	0 to V_{CC}–1.5			0 to V_{CC}–1.5			V
				Full range	0 to V_{CC}–2			0 to V_{CC}–2			
V_{OH}	High-level output voltage	$R_L \geq 2$ kΩ		25°C	V_{CC}–1.5			V_{CC}–1.5			V
		$R_L \geq 10$ kΩ		25°C							
		V_{CC} = MAX	R_L = 2 kΩ	Full range	26			26			
			$R_L \geq 10$ kΩ	Full range	27	28		27	28		
V_{OL}	Low-level output voltage	$R_L \leq 10$ kΩ		Full range		5	20		5	20	mV
A_{VD}	Large-signal differential voltage amplification	V_{CC} = 15 V, V_O = 1 V to 11 V, R_L = ≥ 2 kΩ		25°C	50	100		25	100		V/mV
				Full range	25			15			
CMRR	Common-mode rejection ratio	V_{CC} = 5 V to MAX, $V_{IC} = V_{ICR(min)}$		25°C	70	80		65	80		dB
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{DD}/\Delta V_{IO}$)	V_{CC} = 5 V to MAX		25°C	65	100		65	100		dB
V_{O1}/V_{O2}	Crosstalk attenuation	f = 1 kHz to 20 kHz		25°C		120			120		dB
I_O	Output current	V_{CC} = 15 V, V_{ID} = 1 V, V_O = 0		25°C	–20	–30		–20	–30		mA
				Full range	–10			–10			
		V_{CC} = 15 V, V_{ID} = –1 V, V_O = 15 V		25°C	10	20		10	20		
				Full range	5			5			
		V_{ID} = –1 V, V_O = 200 mV		25°C	12	30		12	30		µA
I_{OS}	Short-circuit output current	V_{CC} at 5 V, GND at –5 V, V_O = 0		25°C		±40	±60		±40	±60	mA
I_{CC}	Supply current (two amplifiers)	V_O = 2.5 V, No load		Full range		0.7	1.2		0.7	1.2	mA
		V_{CC} = MAX, V_O = 0.5 V, No load		Full range		1	2		1	2	

† All characteristics are measured under open-loop conditions with zero common-mode input voltage, unless otherwise specified. MAX V_{CC} for testing purposes is 26 V for LM 2904 and 30 V for others.
‡ Full range is –55°C to 125°C for LM158, –25°C to 85°C for LM258, 0°C to 70°C for LM358, and –40°C to 125°C for LM2904 and LM2904Q.
§ All typical values are at T_A = 25°C.

electrical characteristics at specified free-air temperature, V_{CC} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS†		T_A‡	LM2904 LM2904Q			UNIT
					MIN	TYP§	MAX	
V_{IO}	Input offset voltage	V_{CC} = 5 V to MAX, $V_{IC} = V_{ICR(min)}$, V_O = 1.4 V		25°C		3	7	mV
				Full range			10	
α_{VIO}	Average temperature coefficient of input offset voltage			Full range		7		μV/°C
I_{IO}	Input offset current	V_O = 1.4 V		25°C		2	50	nA
				Full range			300	
α_{IIO}	Average temperature coefficient of input offset current			Full range		10		pA/°C
I_{IB}	Input bias current	V_O = 1.4 V		25°C		–20	–250	nA
				Full range			–500	
V_{ICR}	Common-mode input voltage range	V_{CC} = 5 V to MAX		25°C	0 to V_{CC}–1.5			V
				Full range	0 to V_{CC}–2			
V_{OH}	High-level output voltage	$R_L \geq 2$ kΩ		25°C				V
		$R_L \geq 10$ kΩ		25°C	V_{CC}–1.5			
		V_{CC} = MAX	R_L = 2 kΩ	Full range	26			
			$R_L \geq 10$ kΩ	Full range	23	24		
V_{OL}	Low-level output voltage	$R_L \leq 10$ kΩ		Full range		5	20	mV
A_{VD}	Large-signal differential voltage amplification	V_{CC} = 15 V, V_O = 1 V to 11 V, $R_L = \geq 2$ kΩ		25°C	25	100		V/mV
				Full range	15			
CMRR	Common-mode rejection ratio	V_{CC} = 5 V to MAX, $V_{IC} = V_{ICR(min)}$		25°C	50	80		dB
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{DD}/\Delta V_{IO}$)	V_{CC} = 5 V to MAX		25°C	65	100		dB
V_{O1}/V_{O2}	Crosstalk attenuation	f = 1 kHz to 20 kHz		25°C		120		dB
I_O	Output current	V_{CC} = 15 V, V_{ID} = 1 V, V_O = 0		25°C	–20	–30		mA
				Full range	–10			
		V_{CC} = 15 V, V_{ID} = –1 V, V_O = 15 V		25°C	10	20		
				Full range	5			
		V_{ID} = –1 V,	V_O = 200 mV	25°C		30		μA
I_{OS}	Short-circuit output current	V_{CC} at 5 V, GND at –5 V, V_O = 0		25°C		±40	±60	mA
I_{CC}	Supply current (two amplifiers)	V_O = 2.5 V,	No load	Full range		0.7	1.2	mA
		V_{CC} = MAX, V_O = 0.5 V, No load		Full range		1	2	

† All characteristics are measured under open-loop conditions with zero common-mode input voltage, unless otherwise specified. MAX V_{CC} for testing purposes is 26 V for LM 2904 and 30 V for others.
‡ Full range is –55°C to 125°C for LM158, –25°C to 85°C for LM258, 0°C to 70°C for LM358, and –40°C to 125°C for LM2904 and LM2904Q.
§ All typical values are at T_A = 25°C.

electrical characteristics at specified free-air temperature, V_{CC} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS†		T_A‡	LM158A			LM258A			UNIT
					MIN	TYP§	MAX	MIN	TYP§	MAX	
V_{IO}	Input offset voltage	V_{CC} = 5 V to 30 V, $V_{IC} = V_{ICR(min)}$, V_O = 1.4 V		25°C			2		2	3	mV
				Full range			4			4	
α_{VIO}	Average temperature coefficient of input offset voltage			Full range		7	15*		7	15	µV/°C
I_{IO}	Input offset current	V_O = 1.4 V		25°C		2	10		2	15	nA
				Full range			30			30	
α_{IIO}	Average temperature coefficient of input offset current			Full range		10	200		10	200	pA/°C
I_{IB}	Input bias current	V_O = 1.4 V		25°C		–15	–50		–15	–80	nA
				Full range			–100			–100	
V_{ICR}	Common-mode input voltage range	V_{CC} = 30 V		25°C	0 to V_{CC}–1.5			0 to V_{CC}–1.5			V
				Full range	0 to V_{CC}–2			0 to V_{CC}–2			
V_{OH}	High-level output voltage	$R_L \geq 2$ kΩ		25°C	V_{CC}–1.5			V_{CC}–1.5			V
		V_{CC} = 30 V	R_L = 2 kΩ	Full range	26			26			
			$R_L \geq 10$ kΩ	Full range	27	28		27	28		
V_{OL}	Low-level output voltage	$R_L \leq 10$ kΩ		Full range		5	20		5	20	mV
A_{VD}	Large-signal differential voltage amplification	V_{CC} = 15 V, V_O = 1 V to 11 V, $R_L = \geq 2$ kΩ		25°C	50	100		50	100		V/mV
				Full range	25			25			
CMRR	Common-mode rejection ratio			25°C	70	80		70	80		dB
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{DD}/\Delta V_{IO}$)			25°C	65	100		65	100		dB
V_{O1}/V_{O2}	Crosstalk attenuation	f = 1 kHz to 20 kHz		25°C		120			120		dB

*On products compliant to MIL-PRF-38535, this parameter is not production tested.
† All characteristics are measured under open-loop conditions with zero common-mode input voltage, unless otherwise specified.
‡ Full range is –55°C to 125°C for LM158A, –25°C to 85°C for LM258A, and 0°C to 70°C for LM358A.
§ All typical values are at T_A = 25°C.

electrical characteristics at specified free-air temperature, V_{CC} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS†		T_A‡	LM358A			UNIT
					MIN	TYP§	MAX	
V_{IO}	Input offset voltage	V_{CC} = 5 V to 30 V, $V_{IC} = V_{ICR(min)}$, V_O = 1.4 V		25°C		2	3	mV
				Full range			5	
α_{VIO}	Average temperature coefficient of input offset voltage			Full range		7	20	µV/°C
I_{IO}	Input offset current	V_O = 1.4 V		25°C		2	30	nA
				Full range			75	
α_{IIO}	Average temperature coefficient of input offset current			Full range		10	300	pA/°C
I_{IB}	Input bias current	V_O = 1.4 V		25°C		–15	–100	nA
				Full range			–200	
V_{ICR}	Common-mode input voltage range	V_{CC} = 30 V		25°C	0 to V_{CC}–1.5			V
				Full range	0 to V_{CC}–2			
V_{OH}	High-level output voltage	$R_L \geq 2$ kΩ		25°C	V_{CC}–1.5			V
		V_{CC} = 30 V	R_L = 2 kΩ	Full range	26			
			$R_L \geq 10$ kΩ	Full range	27	28		
V_{OL}	Low-level output voltage	$R_L \leq 10$ kΩ		Full range		5	20	mV
A_{VD}	Large-signal differential voltage amplification	V_{CC} = 15 V, V_O = 1 V to 11 V, R_L = ≥ 2 kΩ		25°C	25	100		V/mV
				Full range	15			
CMRR	Common-mode rejection ratio			25°C	65	80		dB
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{DD}/\Delta V_{IO}$)			25°C	65	100		dB
V_{O1}/V_{O2}	Crosstalk attenuation	f = 1 kHz to 20 kHz		25°C		120		dB

† All characteristics are measured under open-loop conditions with zero common-mode input voltage, unless otherwise specified.
‡ Full range is –55°C to 125°C for LM158A, –25°C to 85°C for LM258A, and 0°C to 70°C for LM358A.
§ All typical values are at T_A = 25°C.

electrical characteristics V_{CC} = 5 V, T_A = 25°C (unless otherwise noted)

PARAMETER		TEST CONDITIONS†			LM358Y			UNIT
					MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{CC} = 5 V to MAX,	$V_{IC} = V_{ICR(min)}$,	V_O = 1.4 V		3	7	mV
I_{IO}	Input offset current					2	50	nA
I_{IB}	Input bias current					–20	–250	nA
V_{ICR}	Common-mode input voltage range	V_{CC} = 5 V to MAX			0 to V_{CC}–1.5			V
V_{OH+}	High-level output voltage	$R_L \geq 10\ k\Omega$			V_{CC}–1.5			V
A_{VD}	Large-signal differential voltage amplification	V_{CC} = 15 V,	V_O = 1 V to 11 V,	$R_L = \geq 2\ k\Omega$	15	100		V/mV
CMRR	Common-mode rejection ratio	$V_{IC} = V_{ICR(min)}$			65	80		dB
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$)				65	100		dB
I_O	Output current	V_{CC} = 15 V	V_{ID} = 1 V,	V_O = 0	–20	–30	–60	mA
			V_{ID} = –1 V,	V_O = 15 V	10	20		
		V_{ID} = 1 V,	V_O = 200 mV		12	30		
I_{OS}	Short-circuit output current	V_{CC} at 5 V,	GND at –5 V,	V_O = 0		±40	±60	mA
I_{CC}	Supply current (four amplifiers)	V_O = 2.5 V,	No load			0.7	1.2	mA
		V_{CC} = MAX,	V_O = 0.5 V,	No load		1	2	

† All characteristics are measured under open-loop conditions with zero common-mode input voltage, unless otherwise specified. MAX V_{CC} for testing purposes is 30 V.

IMPORTANT NOTICE

Texas Instruments and its subsidiaries (TI) reserve the right to make changes to their products or to discontinue any product or service without notice, and advise customers to obtain the latest version of relevant information to verify, before placing orders, that information being relied on is current and complete. All products are sold subject to the terms and conditions of sale supplied at the time of order acknowledgement, including those pertaining to warranty, patent infringement, and limitation of liability.

TI warrants performance of its semiconductor products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

CERTAIN APPLICATIONS USING SEMICONDUCTOR PRODUCTS MAY INVOLVE POTENTIAL RISKS OF DEATH, PERSONAL INJURY, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE ("CRITICAL APPLICATIONS"). TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS. INCLUSION OF TI PRODUCTS IN SUCH APPLICATIONS IS UNDERSTOOD TO BE FULLY AT THE CUSTOMER'S RISK.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards must be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance or customer product design. TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used. TI's publication of information regarding any third party's products or services does not constitute TI's approval, warranty or endorsement thereof.

Copyright © 1998, Texas Instruments Incorporated

LM2904, DUAL GENERAL-PURPOSE OPERATIONAL AMPLIFIER

Device Status: Active

> Description
> Features
> Datasheets
> Pricing/Samples/Availability
> Application Notes
> User Manuals
> Development Tools
> Applications

Parameter Name	LM2904
delta VCC (max) (V)	26
delta VCC (min) (V)	3
IDD / ICC per channel (max) (mA)	0.6
IDD / ICC per channel (typ) (mA)	0.35
GBW (typ) (MHz)	0.4
Slew Rate (typ) (V/us)	0.15
VIO (Full Range) (max) (mV)	10
VIO (25 deg C) (max) (mV)	7
IIB (typ) (pA)	-20000
CMRR (typ) (dB)	80
Vn (typ) (nV/rtHz)	23
Number of Channels	2
Spec'd at VCC (V)	5

Description

These devices consist of two independent, high-gain, frequency-compensated operational amplifiers designed to operate from a single supply over a wide range of voltages. Operation from split supplies also is possible if the difference between the two supplies is 3 V to 30 V (3 V to 26 V for the LM2904 and LM2904Q), and V_{CC} is at least 1.5 V more positive than the input common-mode voltage. The low supply-current drain is independent of the magnitude of the supply voltage.

Applications include transducer amplifiers, dc amplification blocks, and all the conventional operational amplifier circuits that now can be more easily implemented in single-supply-voltage systems. For example, these devices can be operated directly from the standard 5-V supply used in digital systems and easily provides the required interface electronics without additional ±5-V supplies.

The LM2904Q is manufactured to demanding automotive requirements.

The LM158 and LM158A are characterized for operation over the full military temperature range of -55°C to 125°C. The LM258 and LM258A are characterized for operation from -

25°C to 85°C, the LM358 and LM358A from 0°C to 70°C, and the LM2904 and LM2904Q from -40°C to 125°C.

Features

- Wide Range of Supply Voltages:
  - Single Supply...3 V to 30 V (LM2904 and LM2904Q...3 V to 26 V) or
  - Dual Supplies
- Low Supply-Current Drain Independent of Supply Voltage...0.7 mA Typ
- Common-Mode Input Voltage Range Includes Ground, Allowing Direct Sensing Near Ground
- Low Input Bias and Offset Parameters:
  - Input Offset Voltage...3 mV Typ
- A Versions...2 mV Typ
  - Input Offset Current...2 nA Typ
  - Input Bias Current...20 nA Typ
- A Versions...15 nA Typ
- Differential Input Voltage Range Equal to Maximum-Rated Supply Voltage...±32 V (LM2904 and LM2904Q...±26 V)
- Open-Loop Differential Voltage Amplification...100 V/mV Typ
- Internal Frequency Compensation

To view the following documents, Acrobat Reader 3.x is required.
To download a document to your hard drive, right-click on the link and choose 'Save'.

Datasheets

Full datasheet in Acrobat PDF: slos068c.pdf (158 KB)
Full datasheet in Zipped PostScript: slos068c.psz (158 KB)

Pricing/Samples/Availability

Orderable Device	Package	Pins	Temp (°C)	Status	Price/unit USD (100-999)	Pack Qty	DSCC Number	Availability / Samples
LM2904D	D	8	-40 TO 125	ACTIVE	0.34	75		Check stock or order
LM2904DR	D	8	-40 TO 125	ACTIVE	0.28	2500		Check stock or order
LM2904P	P	8	-40 TO 125	ACTIVE	0.34	50		Check stock or order
LM2904PS	PS	8	-40 TO 125	ACTIVE				Check stock or order
LM2904PWLE	PW	8	-40 TO 125	OBSOLETE				
LM2904PWR	PW	8	-40 TO 125	ACTIVE	0.28	2000		Check stock or order
LM2904QD	D	8	-40 TO 125	OBSOLETE				

LM2904QDR	D	8	-40 TO 125	ACTIVE	0.29	2500		Check stock or order
LM2904QP	P	8	-40 TO 125	ACTIVE				Check stock or order

Application Reports

View Application Reports for Operational Amplifiers

- ANALOG APPLICATIONS JOURNAL, FEBRUARY 2000 (SLYT012A - Updated: 03/23/2000)
- ANALOG APPLICATIONS JOURNAL, NOVEMBER 1999 (SLYT010A - Updated: 03/23/2000)
- ANALYSIS OF THE SALLEN-KEY ARCHITECTURE (SLOA024A - Updated: 08/04/1999)
- ELECTROSTATIC DISCHARGE APPLICATION NOTE (SSYA008 - Updated: 05/05/1999)
- SIGNAL CONDITIONING PIEZOELECTRIC SENSORS (SLOA033 - Updated: 10/03/1999)
- SIGNAL CONDITIONING WHEATSTONE RESISTIVE BRIDGE SENSORS (SLOA034 - Updated: 10/03/1999)
- THERMAL CHARACTERISTICS OF LINEAR AND LOGIC PACKAGES USING JEDEC PCB DESIGNS (SZZA017A - Updated: 09/15/1999)

User Manuals

- UNIVERSAL OP AMP EVALUATION MODULE SELECTION GUIDE (SLOU060, 10 KB - Updated: 02/15/2000)
- UNIVERSAL OPERATIONAL AMPLIFIER EVM (SLVU006A, 387 KB - Updated: 04/14/1999)
- UNIVERSAL OPERATIONAL AMPLIFIER SINGLE, DUAL, QUAD (MSOP/TSSOP) (SLOU055, 1196 KB - Updated: 11/11/1999)
- UNIVERSAL OPERATIONAL AMPLIFIER SINGLE, DUAL, QUAD (PDIP) (SLOU062, 1211 KB - Updated: 10/24/1999)
- UNIVERSAL OPERATIONAL AMPLIFIER SINGLE, DUAL, QUAD (SOIC) EVALUATION MODULE WITH (SLOU061, 1160 KB - Updated: 10/24/1999)

Table Data Updated on: 6/2/2000

(c) Copyright 2000 Texas Instruments Incorporated. All rights reserved.
Trademarks, Important Notice!, Privacy Policy

LM358, DUAL GENERAL-PURPOSE OPERATIONAL AMPLIFIER

Device Status: Active

> Description
> Features
> Datasheets
> Pricing/Samples/Availability
> Application Notes
> User Manuals
> Development Tools
> Applications

Parameter Name	LM358
delta VCC (max) (V)	32
delta VCC (min) (V)	3
IDD / ICC per channel (max) (mA)	1
IDD / ICC per channel (typ) (mA)	0.5
GBW (typ) (MHz)	0.4
VIO (Full Range) (max) (mV)	9
VIO (25 deg C) (max) (mV)	7
IIB (typ) (pA)	-20000
CMRR (typ) (dB)	80
Vn (typ) (nV/rtHz)	23
Number of Channels	2
Spec'd at VCC (V)	5

Description

These devices consist of two independent, high-gain, frequency-compensated operational amplifiers designed to operate from a single supply over a wide range of voltages. Operation from split supplies also is possible if the difference between the two supplies is 3 V to 30 V (3 V to 26 V for the LM2904 and LM2904Q), and V_{CC} is at least 1.5 V more positive than the input common-mode voltage. The low supply-current drain is independent of the magnitude of the supply voltage.

Applications include transducer amplifiers, dc amplification blocks, and all the conventional operational amplifier circuits that now can be more easily implemented in single-supply-voltage systems. For example, these devices can be operated directly from the standard 5-V supply used in digital systems and easily provides the required interface electronics without additional ±5-V supplies.

The LM2904Q is manufactured to demanding automotive requirements.

The LM158 and LM158A are characterized for operation over the full military temperature range of -55°C to 125°C. The LM258 and LM258A are characterized for operation from -25°C to 85°C, the LM358 and LM358A from 0°C to 70°C, and the LM2904 and LM2904Q

from -40°C to 125°C.

Features

- Wide Range of Supply Voltages:
  - Single Supply...3 V to 30 V (LM2904 and LM2904Q...3 V to 26 V) or
  - Dual Supplies
- Low Supply-Current Drain Independent of Supply Voltage...0.7 mA Typ
- Common-Mode Input Voltage Range Includes Ground, Allowing Direct Sensing Near Ground
- Low Input Bias and Offset Parameters:
  - Input Offset Voltage...3 mV Typ
- A Versions...2 mV Typ
  - Input Offset Current...2 nA Typ
  - Input Bias Current...20 nA Typ
- A Versions...15 nA Typ
- Differential Input Voltage Range Equal to Maximum-Rated Supply Voltage...±32 V (LM2904 and LM2904Q...±26 V)
- Open-Loop Differential Voltage Amplification...100 V/mV Typ
- Internal Frequency Compensation

To view the following documents, Acrobat Reader 3.x is required.
To download a document to your hard drive, right-click on the link and choose 'Save'.

Datasheets

Full datasheet in Acrobat PDF: slos068c.pdf (158 KB)
Full datasheet in Zipped PostScript: slos068c.psz (158 KB)

Pricing/Samples/Availability

Orderable Device	Package	Pins	Temp (°C)	Status	Price/unit USD (100-999)	Pack Qty	Availability / Samples
LM358D	D	8	0 TO 70	ACTIVE	0.26	75	Check stock or order
LM358DR	D	8	0 TO 70	ACTIVE	0.22	2500	Check stock or order
LM358NS	NS	14	0 TO 70	ACTIVE			Check stock or order
LM358P	P	8	0 TO 70	ACTIVE	0.26	50	Check stock or order
LM358PSLE	PS	8	0 TO 70	OBSOLETE			
LM358PSR	PS	8	0 TO 70	ACTIVE	0.67	2000	Check stock or order
LM358PWLE	PW	8	0 TO 70	OBSOLETE			
LM358PWR	PW	8	0 TO 70	ACTIVE	0.22	2000	Check stock or order

Application Reports

View Application Reports for Operational Amplifiers

- ANALOG APPLICATIONS JOURNAL, FEBRUARY 2000 (SLYT012A - Updated: 03/23/2000)
- ANALOG APPLICATIONS JOURNAL, NOVEMBER 1999 (SLYT010A - Updated: 03/23/2000)
- ANALYSIS OF THE SALLEN-KEY ARCHITECTURE (SLOA024A - Updated: 08/04/1999)
- ELECTROSTATIC DISCHARGE APPLICATION NOTE (SSYA008 - Updated: 05/05/1999)
- SIGNAL CONDITIONING PIEZOELECTRIC SENSORS (SLOA033 - Updated: 10/03/1999)
- SIGNAL CONDITIONING WHEATSTONE RESISTIVE BRIDGE SENSORS (SLOA034 - Updated: 10/03/1999)
- THERMAL CHARACTERISTICS OF LINEAR AND LOGIC PACKAGES USING JEDEC PCB DESIGNS (SZZA017A - Updated: 09/15/1999)

User Manuals

- UNIVERSAL OP AMP EVALUATION MODULE SELECTION GUIDE (SLOU060, 10 KB - Updated: 02/15/2000)
- UNIVERSAL OPERATIONAL AMPLIFIER EVM (SLVU006A, 387 KB - Updated: 04/14/1999)
- UNIVERSAL OPERATIONAL AMPLIFIER SINGLE, DUAL, QUAD (MSOP/TSSOP) (SLOU055, 1196 KB - Updated: 11/11/1999)
- UNIVERSAL OPERATIONAL AMPLIFIER SINGLE, DUAL, QUAD (PDIP) (SLOU062, 1211 KB - Updated: 10/24/1999)
- UNIVERSAL OPERATIONAL AMPLIFIER SINGLE, DUAL, QUAD (SOIC) EVALUATION MODULE WITH (SLOU061, 1160 KB - Updated: 10/24/1999)

Table Data Updated on: 6/2/2000

(c) Copyright 2000 Texas Instruments Incorporated. All rights reserved.
Trademarks, Important Notice!, Privacy Policy