

# BAV70DXV6, NSVBAV70DXV6

## Monolithic Dual Switching Diode Common Cathode

### Features

- NSV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant

### MAXIMUM RATINGS (EACH DIODE)

| Rating                     | Symbol          | Value | Unit |
|----------------------------|-----------------|-------|------|
| Reverse Voltage            | $V_R$           | 100   | Vdc  |
| Forward Current            | $I_F$           | 200   | mAdc |
| Peak Forward Surge Current | $I_{FM(surge)}$ | 500   | mAdc |

### THERMAL CHARACTERISTICS

| Characteristic<br>(One Junction Heated)                                               | Symbol          | Max                                | Unit                       |
|---------------------------------------------------------------------------------------|-----------------|------------------------------------|----------------------------|
| Total Device Dissipation, $T_A = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$ | $P_D$           | 357<br>(Note 1)<br>2.9<br>(Note 1) | mW<br>mW/ $^\circ\text{C}$ |
| Thermal Resistance, Junction-to-Ambient                                               | $R_{\theta JA}$ | 350<br>(Note 1)                    | $^\circ\text{C}/\text{W}$  |
| Characteristic<br>(Both Junctions Heated)                                             | Symbol          | Max                                | Unit                       |
| Total Device Dissipation, $T_A = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$ | $P_D$           | 500<br>(Note 1)<br>4.0<br>(Note 1) | mW<br>mW/ $^\circ\text{C}$ |
| Thermal Resistance, Junction-to-Ambient                                               | $R_{\theta JA}$ | 250<br>(Note 1)                    | $^\circ\text{C}/\text{W}$  |
| Junction and Storage<br>Temperature Range                                             | $T_J, T_{stg}$  | -55 to<br>+150                     | $^\circ\text{C}$           |


Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. FR-4 @ Minimum Pad




ON Semiconductor®

[www.onsemi.com](http://www.onsemi.com)



SOT-563  
CASE 463A

### MARKING DIAGRAM



A4 = Specific Device Code  
M = Month Code  
▪ = Pb-Free Package  
(Note: Microdot may be in either location)

### ORDERING INFORMATION

| Device          | Package              | Shipping†             |
|-----------------|----------------------|-----------------------|
| BAV70DXV6T5G    | SOT-563<br>(Pb-Free) | 8000 / Tape &<br>Reel |
| NSVBAV70DXV6T5G | SOT-563<br>(Pb-Free) | 8000 / Tape &<br>Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.


# BAV70DXV6, NSVBAV70DXV6

## ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise noted) (EACH DIODE)

| Characteristic                                                                                                                                                                              | Symbol     | Min | Max                        | Unit          |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|-----|----------------------------|---------------|
| <b>OFF CHARACTERISTICS</b>                                                                                                                                                                  |            |     |                            |               |
| Reverse Breakdown Voltage (Note 2)<br>( $I_{(BR)} = 100 \mu\text{A}$ )                                                                                                                      | $V_{(BR)}$ | 100 | –                          | Vdc           |
| Reverse Voltage Leakage Current (Note 2)<br>( $V_R = 25 \text{ Vdc}$ , $T_J = 150^\circ\text{C}$ )<br>( $V_R = 100 \text{ Vdc}$ )<br>( $V_R = 70 \text{ Vdc}$ , $T_J = 150^\circ\text{C}$ ) | $I_R$      | –   | 60<br>1.0<br>100           | $\mu\text{A}$ |
| Diode Capacitance (Note 2)<br>( $V_R = 0$ , $f = 1.0 \text{ MHz}$ )                                                                                                                         | $C_D$      | –   | 1.5                        | pF            |
| Forward Voltage (Note 2)<br>( $I_F = 1.0 \text{ mA}$ )<br>( $I_F = 10 \text{ mA}$ )<br>( $I_F = 50 \text{ mA}$ )<br>( $I_F = 150 \text{ mA}$ )                                              | $V_F$      | –   | 715<br>855<br>1000<br>1250 | mVdc          |
| Reverse Recovery Time (Note 2)<br>( $I_F = I_R = 10 \text{ mA}$ , $V_R = 5.0 \text{ Vdc}$ , $I_{R(REC)} = 1.0 \text{ mA}$ ) (Figure 1)                                                      | $t_{rr}$   | –   | 6.0                        | ns            |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

2. For each individual diode while second diode is unbiased.



- Notes: 1. A 2.0 k $\Omega$  variable resistor adjusted for a Forward Current ( $I_F$ ) of 10 mA.  
 2. Input pulse is adjusted so  $I_{R(\text{peak})}$  is equal to 10 mA.  
 3.  $t_p \gg t_{rr}$

**Figure 1. Recovery Time Equivalent Test Circuit**

# BAV70DXV6, NSVBAV70DXV6

## Curves Applicable to Each Anode




Figure 2. Forward Voltage




Figure 3. Leakage Current





Figure 4. Capacitance

# BAV70DXV6, NSVBAV70DXV6

## PACKAGE DIMENSIONS

SOT-563, 6 LEAD  
CASE 463A  
ISSUE F




NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETERS
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.

| DIM            | MILLIMETERS |      |      | INCHES   |       |       |
|----------------|-------------|------|------|----------|-------|-------|
|                | MIN         | NOM  | MAX  | MIN      | NOM   | MAX   |
| A              | 0.50        | 0.55 | 0.60 | 0.020    | 0.021 | 0.023 |
| b              | 0.17        | 0.22 | 0.27 | 0.007    | 0.009 | 0.011 |
| C              | 0.08        | 0.12 | 0.18 | 0.003    | 0.005 | 0.007 |
| D              | 1.50        | 1.60 | 1.70 | 0.059    | 0.062 | 0.066 |
| E              | 1.10        | 1.20 | 1.30 | 0.043    | 0.047 | 0.051 |
| e              | 0.5 BSC     |      |      | 0.02 BSC |       |       |
| L              | 0.10        | 0.20 | 0.30 | 0.004    | 0.008 | 0.012 |
| H <sub>E</sub> | 1.50        | 1.60 | 1.70 | 0.059    | 0.062 | 0.066 |

### SOLDERING FOOTPRINT\*



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

### PUBLICATION ORDERING INFORMATION

**LITERATURE FULFILLMENT:**  
Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada  
**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)  
**Order Literature:** <http://www.onsemi.com/orderlit>  
For additional information, please contact your local Sales Representative

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ON Semiconductor:](#)

[BAV70](#) [BAV70DXV6T1](#) [BAV70DXV6T1G](#) [BAV70DXV6T5](#) [BAV70DXV6T5G](#) [NSVBAV70DXV6T5G](#)