

Uni-Trend Group Limited

UT208A

Registered Design No.: 0411493.0

Digital Clamp Multimeters**SPECIFICATIONS**

Basic Functions	Range	Best Accuracy
DC Voltage	400mV/4V/40V/400V/1000V	±(0.8%+1)
AC Voltage	400mV/4V/40V/400V/750V	±(1.2%+3)
DC Current	40A/400A/1000A	±(1.5%+5)
AC Current	40A/400A/1000A	±(2%+2)
Resistance	400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ	±(1%+2)
Temperature (°C)	-40°C ~ 1000°C	±(2.5%+3)
Capacitance	4nF/40nF/400nF/4μF/40μF/100μF	±(4%+3)
Frequency	10Hz/100Hz/1kHz/10kHz/1MHz/10MHz	±(0.1%+3)
Duty Cycle	0.1% ~ 99.9%	✓
Special Functions		
Auto Ranging		✓
Diode		✓
Continuity Buzzer		✓
True RMS	AC	
Frequency Measurement by Conductor		✓
Data Hold		✓
Sleep Mode		✓
Display Backlight		✓
Low Battery Display		✓
Input Impedance for DC Voltage Measurement	≥10MΩ	✓
Max. Conductor Diameter	55mm	✓
Max. Display	4000	✓

GENERAL CHARACTERISTICS

Power	9V Alkaline Battery
LCD Size	47 x 30mm
Product Colour	Red and Grey
Product Net Weight	533g
Product Size	286 x 105 x 45mm
Standard Accessories	Test Lead, Battery, English Manual, Tool Box, Point Contact Temperature Probe
Standard Individual Packing	Gift Box

*Available at Extra Cost
Specifications and other information are subject to change without further notice.

<http://www.uni-trend.com/UT208A.html>