

Accessories

UT-L01/07/09/11/12/16/17/18

■ UT-L01

- Wire length: 450mm
- Probe length: 5mm
- Temperature condition: -10 °C~40°C
- Suitable for measuring SMT components



■ UT-L07

- Wire length: 1000mm
- Probe length: 17mm
- Double insulation, Banana plug, Adjustable probe
- Temperature condition: -15 °C~40°C



■ UT-L09

- Wire length: 1000mm
- Double insulation, Banana plug, One end with 180 ° connection, One end right angle connection
- Temperature condition: -15 °C~40°C



■ UT-L11

- Wire length: 1000mm
- Double insulation, Banana plug, Two ends with 180 ° connection
- Temperature condition: -15 °C~40°C



■ UT-L12

- Wire length: 1000mm
- Double insulation, Banana plug, Two end with 180 ° connection
- Temperature condition: 0 °C~40°C
- To work as a testing instruments connector



■ UT-L16

- Wire length: 1200mm
- Probe length: 18mm
- Double insulation
- Temperature condition: -20 °C~50°C



■ UT-L17

- Wire length: 1000mm
- Probe length: 16mm
- With LED suitable for working at dim environment
- CAT III 1000V 10A



■ UT-L18

- Wire length: 1000mm
- Probe length: 16mm
- With LED suitable for working at dim environment
- With live wire detector feature
- CAT III 1000V 10A

